

PRODUCT DATA SHEET

ACMEKLIN-2264

A SUPERIOR READY FOR USE ALUMINA COATING FOR STEEL AND IRON FOUNDRIES

INTRODUCTION:

ACMEKLIN-2264 is a Alumina based coating in ready for use consistency. It can be used for brush, spray, dip application and can be extended for flow / flood applications in light steel and iron foundries.

PROPERTIES

1	Colour	White
2	Appearance	Liquid
3	Baume	55 \pm 5
4	B4 cup test	17 \pm 1 Sec
5	Sp. Gravity	1.5 \pm 0.05

APPLICATION DETAILS:

- Remix ACMEKLIN-2264 to homogenize the contents
- If required coating to be diluted with available spirit solvent to suit application consistency
- Flash off the coating for drying purpose.

ADVANTAGES:

- Offers ease of mixing and application
- Ensures uniform coating thickness
- Gives improved casting finish thereby reducing fettling time and cost
- Reduces gas defects due to low gas content in the coating

STANDARD PACKING: Available in 30 kg poly bucket

STORAGE:

- Store in a cool, dry and preferably well ventilated place
- Lids to be replaced tightly to prevent loss due to evaporation

SHELF LIFE: Six months

PRECAUTIONS: Use gloves and nose masks to avoid continuous skin contact and inhalation of the vapors emanating from the coating

Manufactured by:
ACME FOUNDRY FLUX CO.
(An ISO 9001-2015 Certified Company)

264, HADAPSAR INDUSTRIAL ESTATE, PUNE - 411 013 INDIA
Contact: 9422036113 / 9209801514 E-mail: marketing@acmefoundryflux.com