

### PRODUCT DATA SHEET

### **ACMEKLIN-1415XL**

## A HIGH PERFORMANCE VERSATILE ZIRCON COATING FOR STEEL AND FERROUS FOUNDRIES

#### **INTRODUCTION:**

**ACMEKLIN-1415XL** is a Zircon based coating in ready for use consistency. While it is specially designed for flow / flood coating application of moulds and cores, it can be used for brush, spray and dip application in steel / ferrous foundries.

#### **PROPERTIES**

1	Colour	Vilot
2	Appearance	Liquid
3	Baume	75 <u>+</u> 5 deg.
4	Sp. Gravity	1.9 <u>+</u> 0.05

#### **APPLICATION DETAILS:**

- Remix ACMEKLIN-1415XL to homogenize the contents
- If required coating to be diluted with available spirit solvent to suit application consistency
- Flash off the coating for drying purpose

#### **ADVANTAGES:**

- Ensures uniform coating thickness due to its excellent flow ability
- Offers ease of mixing and application due to superior suspension properties
- Gives improved casting surface finish thereby reducing fettling time and cost leading to improved productivity
- Reduces gas defects due to low gas content in the coating

**STANDARD PACKING**: Available in 30 kg poly bucket

#### STORAGE:

- Store in a cool, dry and preferably well ventilated place
- Lids to be replaced tightly to prevent loss due to evaporation

SHELF LIFE: Six months

**PRECAUTIONS**: Use gloves and nose masks to avoid continuous skin contact and inhalation of the vapors emanating from the coating

# Manufactured by: ACME FOUNDRY FLUX CO.

(An ISO 9001-2015 Certified Company)

264, HADAPSAR INDUSTRIAL ESTATE, PUNE - 411 013 INDIA

Contact: +919422036113 / +919209801514 E-mail:marketing@acmefoundryflux.com

Web: www.acmefoudnryflux.in